6. Winch




Small Grand Prix Race Winches

Lightweight and strong, Lewmar's race winches offer the serious racer outstanding performance and power. Using the best features of our standard range, combined with the technology used on Fast 40+, Small Grand Prix Racing Winches offer performance and flexibility in lower-load applications.

All 3-Speed Grand Prix winches are available in either self-tailing, cleat top or sheave base configurations.

- Developed in conjunction with some of the top racing classes including, Fast 40+ and Kerr designs
- Range of finishes, including milled and keronite surfaces
- Driven manually, by power or through a pedestal

Dimensions Diagram Grand Prix Racing Winch





Grand Prix Racing Winch Specifications

PART NO	MODEL	GEAR RATIO 1ST 2ND 3RD 4TH			POWER RATIO 1ST 2ND 3RD 4TH			WEIGHT		DRUM DIA MM IN		BASE DIA MM IN		HEIGHT		LINE ENTRY MM IN		LINE SIZE		MOUNTING INSTRUCTIONS		
49050125	50GPST	3.4:1	11.3:1			15.2:1	50:1			4.7	10.3	115	41/2	188	73/8	168	65/8	62	21/2	8-14	⁵ / ₁₆ - ⁹ / ₁₆	5 X M8 ($^5\!\!/_{16}$ IN) C'SK HEAD SCREWS ON 170MM ($6^5\!\!/_{8}$ IN) PCD
49050130	50GPST SR	3.4:1	11.3:1			15.2:1	50:1			5.1	11.2	115	41/2	217	81/2	168	65/8	62	21/2	8-14	⁵ / ₁₆ - ⁹ / ₁₆	5 X M8 ($^5\!\!/_{16}$ IN) C'SK HEAD SCREWS ON 170MM ($6^5\!\!/_{8}$ IN) PCD
49060000	6o/3GPST	1:1	4.3:1	15.4:1		3.9:1	16.8:1	60.2:1		7.8	17.2	130	51/8	214	81/2	186	73/8	67	25/8	8-14	⁵ / ₁₆ - ⁹ / ₁₆	6 X M8 ($^5\!\!/_{16}$ IN) C'SK HEAD SCREWS ON 195MM ($7^5\!\!/_{8}$ IN) PCD
49060009	60/3GP SB	1:1	4.3:1	15.4:1		3.9:1	16.8:1	60.2:1		8.2	18	130	51/8	236	9 ⁵ ⁄16	186	73/8	67	25/8	8-14	⁵ / ₁₆ - ⁹ / ₁₆	$6 \times M8 (\frac{5}{16} \text{ IN}) \text{ c'sk HEAD SCREWS ON}$ 195MM ($7\frac{5}{8} \text{ IN}) \text{ PCD}$
49068001	68ACSTR	3.5	19.2:1			12:1	67:1			9.5	20.9	150	5 %	250	9 ¹³ /16	213	83/8	99	31/8	8-14	⁵ / ₁₆ - ⁹ / ₁₆	6 x m10 ($^3/_8$ in) c'sk head screws on 200MM ($^7/_8$ in) PCD
49068160	68/3ACSTR	1:1	3.4:1	19.2:1		3.5:1	12:1	67:1		10.6	23.3	146	53/4	250	9 ¹³ /16	227	8 ¹⁵ / ₁₆	97	31/8	8-14	⁵ / ₁₆ - ⁹ / ₁₆	6 X M10 (3 /8 IN) C'SK HEAD SCREWS ON 200MM (7 /8 IN) PCD
49068021	68/3GP SB	1:1	3.5:1	19.3:1		3.5:1	12:1	67:1		10.5	23.1	146	53/4	275	10 ¹³ / ₁₆	227	8 ¹⁵ / ₁₆	95	3¾	8-14	⁵ / ₁₆ - ⁹ / ₁₆	6 x m10 ($^3/_8$ in) c'sk head screws on 200mm ($^7/_8$ in) pcd

SR - SPEED RING | ST- SELF TAILING | SB - SHEAVE BASE